

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
25 August 2005 (25.08.2005)

PCT

(10) International Publication Number
WO 2005/078547 A1

(51) International Patent Classification⁷: **G05G 1/14**

(74) Agents: **WALLENGREN, Yngvar** et al.; Patentbyrå Y Wallengren AB, Box 116, S-331 21 Värnamo (SE).

(21) International Application Number:
PCT/SE2005/000076

(22) International Filing Date: 25 January 2005 (25.01.2005)

(25) Filing Language: Swedish

(26) Publication Language: English

(30) Priority Data:
0400135-0 26 January 2004 (26.01.2004) SE

(71) Applicant (for all designated States except US): **TELE-FLEX AUTOMOTIVE SWEDEN AB** [SE/SE]; Skogarsvägen 2, S-514 63 Dalstorp (SE).


(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,

(72) Inventor; and
(75) Inventor/Applicant (for US only): **JOHANSSON, Matias** [SE/SE]; Knestorp Källeberg, S-514 61 Dalstorp (SE).

[Continued on next page]

(54) Title: A PEDAL SUPPORT



(57) Abstract: The disclosure relates to a pedal support for a vehicle, comprising a bracket (9) which is secured in a bulkhead disposed in the vehicle between the passenger compartment of the vehicle and the engine room; a first shaft (3) secured in the bracket and horizontal and transversely directed in relation to the direction of travel of the vehicle; a pedal arm (2) provided with a footplate (23) and pivotal about the first shaft; an operating device (22) which is secured in the arm (2) a distance from the first shaft and which is disposed for manoeuvring or controlling a vehicle function, for example a braking function. According to the invention, the first shaft (3) is movably disposed in the bracket (9) in the direction of travel of the vehicle, the first shaft having a normal position locked by means of a locking device (13), and the locking device being, in the event of a collision, openable for permitting displacement of the first shaft (3) to a safety position where the footplate (23) is displaced away from the legs/feet of the vehicle driver but where the function of the operating device (22) is at least partly retained.



SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*